

LKM-935/9358


15"LCD 5-in-1 1U Height Drawer with Individual Monitor and Keyboard module

Individual for LCD Display and Keyboard!
Five functions: LCD monitor, keyboard, mouse, speaker and KVMA switch

**Coming
Soon**



Individual for LCD display and keyboard module



Two self-click prevents the keyboard from sliding in shaking



No special cables required, up to 8 computers connection!



LKM-CBXXA

LKM-935/9358

LKM-935/9358 Space saving measure for standard 19" rack-mount application has been maximized. The all-in-one 1U product from IEI supports one 15" LCD screen, touch pad, speakers and keyboard. Traditional LKM products require that the LCD monitor and keyboard be either both retracted or both exposed. The new and improved LKM-935/9358 allows user to operate the keyboard and LCD monitor separately. When the keyboard is not in use, the user can retract the keyboard alone, leaving the LCD display exposed for continued monitoring, yet saved valuable space for the user.

Specifications

- ◆ 1U Height designed to save rack space
- ◆ Individual Monitor and Keyboard module
- ◆ 15" high brightness TFT LCD display
 - Display type : XGA TFT
 - Resolution : 1024x768
 - Support color : 262k color
 - Brightness : 200cd/m²
 - Contrast Ratio : 250:1(Typ)
 - Pixel Pitch : 0.297(H)x0.297(W)
 - Viewing Angle : 120°(Horizontal) , 90°(Vertical)
 - LCD MTBF : 50,000 hrs
 - Backlight MTBF : 25,000 hrs
- ◆ 88key with slim size keyboard , supports English Japanese German French Italian version keyboard
- ◆ Touch pad with two key buttons
- ◆ Accept audio input and built-in two speakers
- ◆ The front panel shall include two captives screws in the lock
- ◆ Built-in OSD for user adjustment , including , H/V position , color ,size,...etc
- ◆ Power Supply
 - Built-in universal AC Input 46W adapter
 - ACE-802T , 36VDC~72VDC input 12V@2A output
 - ACE-802C , 20VDC~30VDC input 12V@2A output
- ◆ Depth:536mm
- ◆ Operating Temperature :0~50°C

Main Features

- ◆ Outstanding LCD module: channel change control, auto scan control, editable station name.
- ◆ KVMA switch: 8 port KVMA switch can be manually or auto-metrically set via LCD module
- ◆ Standard support of English version keyboard, Option Japanese, German, French, Italian version keyboard support
- ◆ Embedded within speaker specified on alarm warning notice or audio application
- ◆ Hot-pluggable-Add or remove computers without having to power down the switch
- ◆ Individual Monitor and Keyboard module

Ordering Information

- LKM-935 [C]-[L]
Single Input 15.1" LCD/Keyboard/Mouse/Speaker 1U drawer AC Input with individual Monitor and Keyboard module
 - LKM-935 [C]-[T]-[L]
Single input 15.1" LCD/Keyboard/Mouse/Speaker 1U drawer 48VDC Input with individual Monitor and Keyboard module
 - LKM-935 [C]-24V-[L]
Single input 15.1" LCD/Keyboard/Mouse/Speaker 1U drawer 24VDC Input with individual Monitor and Keyboard module
 - LKM-9358 [C]-[L]
8 input 15.1" LCD/Keyboard/Mouse/Speaker 1U drawer AC Input with individual Monitor and Keyboard module
 - LKM-9358 [C]-[T]-[L]
8 input 15.1" LCD/Keyboard/Mouse/Speaker 1U drawer 48VDC Input with individual Monitor and Keyboard module
 - LKM-9358 [C]-24V-[L]
8 input 15.1" LCD/Keyboard/Mouse/Speaker 1U drawer 24VDC Input with individual Monitor and Keyboard module
- [C] : Color Code B: Black W: White
[L] : Language Code EN: English JP: Japanese DE: German FR: French IT: Italian

IEI Option

- KVM-008B Extend KVMA Box for LKM-9268A
- LKM-CB18A 1.8M cable set; includes VGA, Keyboard, Mouse and Audio cable.
- LKM-CB30A 3.0M cable set; includes VGA, Keyboard, Mouse and Audio cable.
- LKM-CB50A 5.0M cable set; includes VGA, Keyboard, Mouse and Audio cable.



ICP Deutschland GmbH
Industrial Computer Products
Humboldtstr. 36
D - 70771 Leinfelden-Echterdingen

Tel.: +49 (0)711-45 96 00 30
Fax: +49 (0)711-45 96 00 50
http://www.icp-deutschland.de
info@icp-deutschland.de

